



Product Service

CERTIFICATE

No. Z1A 019959 0114 Rev. 01

Factories: 019959

Model(s): UniCompact
 5002; 5003; 5004; 5005; 5006; 5007; 5008
 UniCompact P2
 1405001; 1405002; 1405003; 1405004; 1405005;
 1405006; 1405007; 1405008; 1405022; 1405023;
 1405024; 1405025; 1405026; 1405027; 1405028

Parameter:

UniCompact	mobile working towers
max. load:	2,0 kN/m ² (scaffold group 3)
dimension:	1,50 x 1,80 m
article-no.	Standing height
5002	2,20 m
5003	3,20 m
5004	4,20 m
5005	5,20 m
5006	6,38 m
5007	7,38 m
5008	8,38 m
material	EN AW 6063-T66 / EN AW 6082-T5

UniCompact P2	mobile working towers
max. load:	2,0 kN/m ² (scaffold group 3)
dimension:	1,50 x 1,80 m
article-no.	standing height
1405001	1,20 m
1405002	2,20 m
1405003	3,20 m
1405004	4,20 m
1405005	5,20 m
1405006	6,38 m
1405007	7,38 m
1405008	8,38 m
material	EN AW 6063-T66 / EN AW 6082-T5

TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD
 ZERTIFIKAT ◆ CERTIFICATE ◆ 認證書 ◆ CERTIFICADO ◆ CERTIFICAT





Product Service

CERTIFICATE

No. Z1A 019959 0114 Rev. 01

UniCompact P2	mobile working towers with outrigger
max. load:	2,0 kN/m ² (scaffold group 3)
dimension:	1,50 x 1,80 m
article-no.	standing height
1405022	2,20 m
1405023	3,20 m
1405024	4,20 m
1405025	5,20 m
1405026	6,20 m
1405027	7,20 m
1405028	8,20 m
material	EN AW 6063-T66 / EN AW 6082-T5

TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD
ZERTIFIKAT ♦ CERTIFICATE ♦ 認證書 ♦ СЕРТИФИКАТ ♦ CERTIFICADO ♦ CERTIFICAT