ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ СЕРТИФИКАТ ◆ CERTIFICADO ◆ CERTIFICAT

Product Service

# CERTIFICATE

**No. Z1A 019959 0113 Rev. 01**

**Holder of Certificate:** **Wilhelm Layher GmbH & Co. KG**
Ochsenbacher Straße 56
74363 Güglingen-Eibensbach
GERMANY

**Certification Mark:**

**Product:** **Mobile scaffold**
**Mobile access and working Towers (UniLight)**

**Tested according to:**
DIN EN 1004:2005
DIN EN 1298:1996
PPP 52015B:2016

The product meets the safety and health requirements of the German Product Safety Act section 20 to 22 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. See also notes overleaf.

**Test report no.:** 028-713168325-004

**Valid until:** 2025-01-21

**Date,** 2020-02-20 ( Günther Kahlert )


TÜV SÜD Product Service GmbH • Certification Body • Ridlerstraße 65 • 80339 Munich • Germany

A4 / 07.17

ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ СЕРТИФИКАТ ◆ CERTIFICADO ◆ CERTIFICAT
TÜV SÜD

Product Service

# CERTIFICATE

## No. Z1A 019959 0113 Rev. 01

**Factories:** 019959

**Model(s):**

**UniLight**
**3202; 3203; 3204; 3205; 3206; 3207**
**UniLight P2**
**1403201; 1403202; 1403203; 1403204;**
**1403205; 1403206; 1403207; 1403222;**
**1403223; 1403224; 1403225; 1403226; 1403227**

**Parameter:**

| **UniLight** | mobile working towers |
|---|---|
| max. load: | 2,0 kN/m$^2$ (scaffold group 3) |
| dimension: | 0,75 x 1,80 m |
| article-no. | standing height |
| 3202 | 2,26 m |
| 3203 | 3,26 m |
| 3204 | 4,26 m |
| 3205 | 5,26 m |
| 3206 | 6,26 m |
| 3207 | 7,26 m |
| material | EN AW 6063-T66 / EN AW 6082-T5 |

| **UniLight P2** | mobile working towers |
|---|---|
| max. load: | 2,0 kN/m$^2$ (scaffold group 3) |
| dimension: | 0,75 x 1,80 m |
| article-no. | standing height |
| 1403201 | 1,11 m |
| 1403202 | 2,26 m |
| 1403203 | 3,26 m |
| 1403204 | 4,26 m |
| 1403205 | 5,26 m |
| 1403206 | 6,26 m |
| 1403207 | 7,26 m |
| material | EN AW 6063-T66 / EN AW 6082-T5 |

| **UniLight P2** | mobile working towers with outrigger |
|---|---|
| max. load: | 2,0 kN/m$^2$ (scaffold group 3) |
| dimension: | 0,75 x 1,80 m |
| article-no. | standing height |
| 1403222 | 2,10 m |
| 1403223 | 3,10 m |
| 1403224 | 4,10 m |
| 1403225 | 5,10 m |
| 1403226 | 6,10 m |
| 1403227 | 7,10 m |
| material | EN AW 6063-T66 / EN AW 6082-T5 |


TÜV SÜD Product Service GmbH • Certification Body • Ridlerstraße 65 • 80339 Munich • Germany

TÜV®